

## Data sheet for three-phase Squirrel-Cage-Motors

MLFB-Ordering data : 1LA7083-6AA11

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :

### Electrical data:

Rated voltage :	(1) 230 VD/400 VY, 50 Hz, 460 VY, 60 Hz					
Frequency :	50 Hz		60 Hz			
Rated power :	0.55 kW		0.63 kW			
Rated speed :	910 1/ min		1110 1/ min			
Rated torque :	5.8 Nm		5.4 Nm			
Rated current (IE) :	VD	VY			VY	
	2.78 A	1.60 A			1.60 A	
Starting / rated current :	3.4		3.7			
Breakdown / rated torque :	2.2		2.2			
Starting / rated torque :	2.1		2.1			
	4/4	3/4	2/4	4/4	3/4	2/4
Efficiency %	67.5%	67.0%	63.5%	67.5%	67.0%	63.5%
Power factor :	0.74	0.68	0.55	0.73	0.67	0.54
Efficiency class :	-/		-/			

### Mechanical data:

Sound pressure level 50Hz/60Hz (load) :	40 dB(A)	44 dB(A)
Moment of inertia :	0.0017 kg*m <sup>2</sup>	
Bearing DE :	6004 2ZC3	
Bearing NDE :	6004 2ZC3	
Type of bearing :	Floating bearings pre-loaded DE (standard)	
Condensate drainage holes :	No	
Regreasing device :	No	
Lubricants :	Esso Unirex N3	
Grease lifetime/Relubrication interval :	40000 h	
Quantity of grease for relubrication :	null g	
External earthing terminal :	No	
Coating :	Special paint finish RAL 7030 stone gray	

### Environmental conditions:

Ambient temperature :	-20 °C - +40 °C
Altitude above sea level :	1000 m
Standards and specifications :	IEC, DIN, ISO, VDE, EN

### General data:

Frame size	080 M
Design of electrical machine :	(1) IM B5 / V1 without canopy
Weight in kg, without optional accessories :	10.00 kg
Frame material :	Aluminum
Degree of protection :	IP 55
Method of cooling, TEFC :	IC 411
Vibration class :	A (Standard)
Insulation :	155(F) to 130(B)
Duty type :	S1 - continuous duty
Direction of rotation :	Bi-directional

### Terminal box:

Material of terminal box :	
Type of terminal box :	gk 030
Contact screw thread :	
Max. cross-sectional area :	
Cable diameter from ... to ... :	
Cable entry :	
Cable gland :	

### Special design:

کنترل سازان  
تامین تجهیزات برق صنعتی و الکتروموتور  
شماره های تماس : ۰۲۱-۳۳۱۱۰۷۶۸