

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1130C

SIMOTICS GP - 132 S - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	3.00	-/-	7.30	955	30.0	79.7	79.9	77.1	0.74	0.66	0.52	4.6	2.0	2.6	IE1
690	Y	50	3.00	-/-	4.25	955	30.0	79.7	79.9	77.1	0.74	0.66	0.52	4.6	2.0	2.6	IE1
460	Δ	60	3.45	-/-	6.90	1150	28.5	83.5	83.7	81.4	0.75	0.67	0.55	4.6	1.9	2.3	IE1

IM B3 / IM 1001	FS 132 S	IP55	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
-----------------	----------	------	--------------	------------------------

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 12.1 s | 23.8 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 75 dB(A) ²⁾	67 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.0170 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6208 2Z C3	6208 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad} , min 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	aluminum
Lubricants	Unirex N3		Net weight of the motor (IM B3)	34 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
Condensate drainage holes	No		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	No			

Terminal box

Terminal box position	top	Max. cross-sectional area	6 mm ²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 H00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

کنترل سازان
تامین تجهیزات برق صنعتی و الکتروموتور
شماره های تماس : ۰۲۱-۳۳۱۱۰۷۶۸

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

SIEMENS	document type datasheet	document status released	customer	
	title 1LE1002-1CC03-4AA4	document number		
© Siemens AG 2021	rev. 01	creation date 2021-10-05 01:05	language en	Page 1/1