

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV1182B

SIMOTICS SD - 180 M - IM B3 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η ³⁾			$\cos\phi$ ³⁾			I_A/I_N I_i/I_N	M_A/M_N T_i/T_N	M_K/M_N T_B/T_N	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4				
400	Δ	50	18.50	-/-	35.00	1468	120.0	89.3	90.2	90.2	0.85	0.82	0.73	7.3	2.2	3.1	IE1
690	Y	50	18.50	-/-	20.50	1468	120.0	89.3	90.2	90.2	0.85	0.82	0.73	7.3	2.2	3.1	IE1
460	Δ	60	21.30	-/-	34.50	1768	115.0	91.0	91.9	91.8	0.85	0.82	0.74	7.6	2.2	3.2	IE1

IM B3 / IM 1001 FS 180 M IP55 IEC/EN 60034 IEC, DIN, ISO, VDE, EN

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 8.67 s | 14.4 s

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 76 dB(A) ²⁾	65 / 79 dB(A) ²⁾	Vibration severity grade	A
Moment of inertia	0.1300 kg m ²		Insulation	155(F) to 130(B)
Bearing DE NDE	6210 Z C3	6210 Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} , F _{Rad} min 50 60Hz ¹⁾ for coupling operation	40000 h	32000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	170 kg
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(A) without (Standard)
Condensate drainage holes	Yes (standard)		Method of cooling	IC411 - self ventilated, surface cooled
External earthing terminal	Yes (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5
Contact screw thread	M5	Cable gland	2 plugs

کنترل سازان
تامین تجهیزات برق صنعتی و الکتروموتور
شماره های تماس : ۰۲۱-۳۳۱۱۰۷۶۸

Notes:
 I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque
 1) L10mh according to DIN ISO 281 10/2010
 2) at rated power / at full load
 3) Value is valid only for DOL operation with motor design IC411

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
-------------------------------	---------------------	-------------------------------	-------------	--

SIEMENS	document type datasheet	document status released	customer	
	title 1LE1502-1EB23-4AA4	document number		
© Siemens AG 2021		rev. 01	creation date 2021-10-04 23:57	language en
				Page 1/1